



MICROSAFE®



FEATURES

- ✓ Very simple to use.
- ✓ Unique design.
- ✓ Display showing percentage ON time (1-99%).
- ✓ Adjustment up/down of regulator power controlled by button.
- ✓ Sparkless relay offers superior reliability, low heat generation and virtually silent switching.

PARAMETER MENU

For products made after 19.11.2012

- Menu > Press - and ON/OFF simultaneously
- Scroll > Press ON/OFF button
- Select > Press +/-
- Reset > Press ON/OFF, + and - simultaneously

MENU	FUNCTION	VALUE
Pb	Display brightness	0-50

Microsafe® MReg, Regulator

The MReg shows the percentage ON time on the digital display.

The ON time is simple to adjust using the + and - buttons.



The MReg is available in both a 1-pole 3600 VA and a 2-pole 2300 VA version.


THE REGULATION PERIOD

is 15 min. If you set 33%, the regulator will be on for 5 min. and off for 10 min.

The perfect project regulator

PART NO.	NAME	
5450329	MReg	16A/3600VA 1P
5450333	MReg	16A/2300VA 2P

WIRING DIAGRAM



TECHNICAL DATA			
Physical dimensions:	Conforms to RS16	Reg. power:	1-99%
Voltage:	230 VAC +10/-20%	Backup:	Approx. 2 hours
Max. load:	2,300/3,600 VA	Fuse:	16 A

MANUFACTURER
CTM Lyng AS
Tel: +47 7283 1611
www.ctmlyng.no

