

1/2" Solenoid Valve









FEATURES

- ✓ Wireless communication.
- ✓ Simple to install.
- Controlled by 12 VDC pulse from valve driver.
- ✓ The valve driver runs off 230 V.

COMPATIBLE WITH

- ✓ Moisture Sensor
- ✓ Motion Sensor, wireless
- ✓ Master On/Off, wireless
- ✓ Timer, wireless

1/2" Solenoid Valve

The Aqua Xpress Valve controls the water supply to the house.

The driver can control 2 valves for apartments without a water heater.

The valve is supplied open and remains in the position in which it has been set until it receives a pulse with the opposite polarity.

Cable and plug for valve driver included.


Aqua Xpress is a flexible product that can be expanded to accommodate different needs and security levels.

PART NO.	NAME
5648513 / 6251629	1/2" Solenoid Valve

VALVE				
Dimensions:	HxWxL 84 x 45 x 59 m	nm	Operatingvoltage:	12 VDC
Coil:	Bistable		Pressure/Flow:	0.15 – 10 bar / 42 l/min.
Connection:	IN: %" female thread	OUT:	%" female thread	

VALVE DRIVER					
Dimensions:	HxWxD 95 x 73 x 37 mm	Frequency:	868.100 MHz		
Operating voltage:	230 VAC +10/-20%	Transmitter power:	+5 dBm		

WIRING DIAGRAM



MANUFACTURER

CTM Lyng AS Tel: +47 72 83 16 11 www.ctmlyng.com